

**FRAMING PROJECTOR**


**L2756 Low Voltage Framing Projector with Integral 12V Electronic Transformer**

Notes: Not for use with Four Circuit Trac



**Finish:** White (P), Black (MB)

**Lamp:** 75W 12V MR16

**Accessories:** L256 Iris




Max. Extension:  
11 1/2" (292mm)



**L2756 Framing Projector -Illumination on Vertical Plane**

Lamp Type	Lamp Beam	Distance From Wall	Aiming Angle	Beam Length	Beam Width	Beam Distance From Ceiling	Max Footcandles	Lamp Type	Lamp Beam	Distance From Wall	Aiming Angle	Beam Length	Beam Width	Beam Distance From Ceiling	Max Footcandles
75W EYC	42°	2'	30°	17"	15"	14"	155	50W EXZ	27°	2'	30°	37"	29"	15"	183
			45°	25"	24"	22"	88				45°	30"	15"	22"	96
			60°	50"	39"	32"	35				60°	57"	20"	34"	38
	3'	30°	27"	21"	16"	58	30°		31"	24"	16"	54			
		45°	40"	25"	30"	33	45°		51"	27"	26"	29			
		60°	40"	31"	18"	29	60°		42"	31"	18"	28			
75W EYF	14°	2'	30°	18"	14"	15"	270	50W EXT	14°	2'	30°	19"	15"	14"	178
			45°	32"	16"	22"	139				45°	28"	16"	21"	95
			60°	58"	19"	32"	64				60°	59"	20"	32"	45
	3'	30°	32"	24"	17"	91	30°		30"	24"	16"	62			
		45°	48"	25"	28"	55	45°		51"	27"	26"	30			
		60°	44"	33"	19"	48	60°		46"	34"	17"	30			
50W EXN	40°	2'	30°	17"	13"	15"	156								
			45°	26"	15"	22"	82								
			60°	50"	19"	31"	36								
	3'	30°	27"	21"	17"	56									
		45°	47"	21"	28"	30									
		60°	47"	21"	28"	30									



Width and length of beam is measured to visual cutoff.  
Width and length can be adjusted to fit object by using built in shutters or L256 accessory iris lens.  
The DD value is the distance from ceiling to top edge of beam.  
Footcandle values are averages of lamps from different manufacturers as measured at center of beam.


**WALL WASHERS**

**L1751 Wall Washer with Black Louver**

Notes: Provides broad uniform illumination

**Finish:** White with Black Louver (P)

**Lamp:** 100W A19, 150W A21



Max. Extension:  
7 3/4" (197mm)




**L1752 Quartz Wall Washer**

Notes: Provides uniform illumination with sharp cutoff at top and bottom


**Finish:** White (P), Black (MB)

**Lamp:** 150W T-4 Tungsten Halogen Frosted  
Mini-Candelabra Base

**Accessories:** L977 Barn Doors



Max. Extension:  
6 1/2" (165mm)



**Lampholder/Track Compatibility**

L2756	Halo Single and 2-Circuit	Lazer Track
	L650, L651, L652, L653 L641, L642, L643 L611, L612, L613 L1631, L1632	LZR102, LZR104, LZR106, LZR108

**Lampholder/Track Compatibility**

L1751 L1752	Halo Single and 2-Circuit	Lazer Track
	L650, L651, L652, L653 L641, L642, L643 L611, L612, L613 L1631, L1632	LZR102, LZR104, LZR106, LZR108